

RLD10

REFRIGERANT GAS LEAK DETECTOR



Small, handy and easy-to-use refrigerant leak detector for detecting the most common refrigerants. The 45 cm long and flexible gooseneck is ideal for finding leaks even in hard-to-reach places. Leaks can be precisely located with the two sensitivity modes.

FEATURES

- Tick rate for fast leak detection
- LEDs to indicate the leak rate
- Adjustable sensitivity
- Automatic zero point adjustment
- Fast response time (< 1 second)
- Low weight
- Protective cover
- Detects all halogen-containing refrigerants

SPECIFICATIONS

Refrigerants	CFC, HFC, HCFC, such as R11, R12, R13, R22, R23, R113, R114, R134A, R500, R502, R404A, R410A and many more. <i>Please contact us for other gases.</i>
Power Supply	9V DC block battery
Operating Time	approx. 8 hours
Sensitivity	14g per year R134A
Warm-Up	10 seconds
Response Time	1 second
Alarm Indicators	LEDs, Tickrate
Dimensions in mm	200 x 100 x 38 mm
Flexible Probe	450 mm
Operating Conditions	0 – 40°C / 10 – 80 % rh, non-condensing

ACCESSORIES

AC501	Case for the leak detector
--------------	----------------------------



IM Environmental Equipment Germany GmbH reserves the right to make technical changes.