

MGS-402 Gas Detection Controller

2-Channel Controller for Refrigerant, Toxic and Combustible Gas Detection



DESCRIPTION

Bacharach's MGS-402 Gas Detection Controller centralizes the status of up to two MGS-410 Gas Detectors, provides a complete package for your safety compliance application. On the front panel of the MGS-402 a bank of LEDs corresponds to each connected gas detector; showing power, alarm status and fault indicators. The MGS-402 can provide the power requirements for up to two gas detectors, which can be daisy-chained with Modbus communication to each gas detector; simplifying and reducing the cost of installation.

Combining the MGS-402 Gas Detection Controller with Bacharach's MGS-410 Gas Detector provides a complete, single source gas detection system with an easy means of achieving compliance with refrigeration safety standards such as EN 378 and ASHRAE 15.

FEATURES

LED status indication for "at-a-glance" system / alarm status

Seamless integration with MGS-410 Gas Detector

Controller power up to two MGS-410 Gas Detectors

Modbus RTU Master / Slave provides seamless integration from connected gas detectors to many third-party BMS / BAS

Audible and visual alarms enable compliance with ASHRAE 15 / EN 378 - no additional hardware required

HOW TO CONTACT US:

US Customer Service: +1 724 334 5000

EU Customer Service: +353 1 284 6388

CAN Customer Service: +1 905 882 8985

IM Env. Equip. Germany GmbH
In der Klinge 5/2

D - 74078 Heilbronn - Germany


www.imgmbh.de - Tel. +49 7131 200064

mybacharach.com

| SPECIFICATIONS | DESCRIPTION |
|-----------------------|---|
| Enclosure Rating | IP66 |
| Operating Temperature | -40 - 113°F (-40 - 50°C) |
| Power | 100 - 240 VAC, 50/60 Hz, 20W (max); 24 VDC |
| Size (W×H×D) Approx. | 6.5 × 6.5 × 3.4" (165 × 165 × 87mm) |
| Weight Approx. | 1 lb, 11.07 oz (758 g) |
| Cable Entries | 2 × M20 / 1/2" Conduit (Power), 6 × M16 Cable Glands (Communications) |
| Approvals | CE, UL / CSA / IEC EN 61010-1 |

| PRODUCT DETAILS | DESCRIPTION |
|---------------------|---|
| User Interface | Front Panel Push Buttons; DIP switches |
| Configurable Relays | 1 × Low Alarm, 1 × High Alarm, 1 × Fault (240 VAC @ 10A) |
| Analog Output | 2 × Configurable 4-20mA, 1-5, 2-10VDC |
| Alarm Silence | 2 × Front Panel Push Buttons, 1 × Auxiliary Input |
| Serial Ports | 1 × RS485 Modbus RTU Slave for BMS / BAS, 1 × RS485 Modbus RTU Master for Gas Detectors |

| PART NUMBERS | DESCRIPTION |
|--------------|--------------------|
| 6702-8020 | MGS-402 Controller |



IM Env. Equip. Germany GmbH
 In der Klinge 5/2 - D - 74078 Heilbronn - Germany
 www.imgmbh.de - Tel. +49 7131 200064



Pittsburgh, PA USA | Dublin, IRE | Stanardsville, VA, USA | Toronto, CAN
 mybacharach.com | help@mybacharach.com