

MGS 24VDC 40W External Power Supply

24VDC Power Supply Module




DESCRIPTION

Bacharach's external power supply for any 24V MGS-400 series gas detector or controller such as the MGS-402, MGS-408, MGS-410, MGS-450, and MGS460. The 24V power supply provides increased electrical safety with a solid enclosure that is easy to connect. The power supply is universally applicable offering a wide range of supply voltage (85 to 264 VAC) making it compatible with most applications.

SPECIFICATIONS	DESCRIPTION
Enclosure Rating	IP65
Operating Temperature	-30 - 40°C (-22 - 104 °F)
Power	INPUT: 85 - 264 VAC / 50 - 60 Hz, OUTPUT: 24VDC (1.67A)
Power Input	Terminal Block or RJ45 (Power Over Modbus)
Size (W×H×D)	166 × 83.8 × 59mm (6.54 × 3.30 × 2.32")
Weight	395 g (0.871 lbs)
Cable Entries	Gland Plug
Approvals	CE, Low Voltage Directive 2014/35/EC EMC Directive 2014/30/EC: Emission Standards: EN55022(CISPR22) Class B and EN61000-3-2,3; Immunity standards: EN61000-4-2,3,4,5,6,8,11 and EN55024, Heavy industry Level criteria A WEEE Directive 2012/19/EC RoHs Directive 2011/65/EC

PART NUMBERS	DESCRIPTION
1100-1089	24VDC Power Supply Module

Inputs

85- 264 VAC



Outputs

24 VDC

IM Environmental Equipment Germany GmbH

In der Klinge 5/2 | 74078 Heilbronn | Germany
Tel.: +49 7131 200064 | Fax: +49 7131 200066
info@imgmbh.de | www.im-gasanalysis.com



**Ingeniously
sMART**